Mira/180

Compact mobile lifter



Primary application

Home care Nursing homes Hospitals

Mira is a new, compact, general purpose mobile lifter from Ergolet. The elegant twin mast design gives increased solidity and as with all Ergolet products, the Mira is characterised by its elegant Scandinavian design and simple functionality.

Mira has been designed to easily cope with most lifting situations. The Linak electronics incorporate an on board charger with emergency & manual lowering functions. The design and shape of the chassis and lifting arm give an exceptional lift range (42-177cm - 17-70").

The compact dimensions and high safe working load (180 kg - 28.5 st) ensure that Mira is suitable for home care, care homes and hospital use. The spreader bar is equipped with the unique Ergolet hook system.

Key standard functions

Powered base Built in charger Emergency stop Electric and manual emergency lower

Accessories

Comprehensive range of ERGO slings Spreader bars Weigh scale





Patented Ergolet sling hooks on the spreader bar. Sling attachment: a minimum of downward pressure locks the sling hook; pull upwards to unlock sling hook.



Simple management of emergency stop and lowering and battery charge. Connect directly to wall socket for charging.



Powered leg spreading (V-shape) of wheel base for better access and stability.



The compact mobile lift Mira/180 with user. Lifting arm with large lifting range, 42-177 cm (17-70")

Version	lten number
Mira 180 mobile lift	010-01910
Mira 180 mobile lift - in UK	010-01911UK

TECHNICAL SPECIFICATION

 Max. last
 180 kg (397 lbs, 28.5st)

 Lifting range
 42-177 cm (17-70")

 Total lifts
 approx. 80 lifts at 80 kg (175 lbs) load

External width of base 64-108 cm (25-43") Internal width of base 52-96 cm (20-38")

Height of base 14.5 cm (6") 100 mm (4") wheels

safety class

safety class:

Compliant with

Hand control/battery

12.5 cm (5"), 75 mm (3") wheels
Lenght of base
110 cm (43")
Turning radius
approx. 126 cm (50")
Total weight
42.2 kg (93 lbs)
Chassis
Powder-coated steel
Motor/electrical box

IP43

IP65

ISO 10535, EN 60601-1, EN 60601-1-2, EN 60068-2-32, MDD 93/42/EEC



Consult the Technical manual for further specifications. All figures and measurements are for guidance only and may differ in actual situations. Ergolet reserves the right to changes without notice.

Product photos may include accessories. Consult your dealer.



Ergolet Head Office Taarnborgvej 12C 4220 Korsoer Denmark

Tel. +45 70 27 37 20 e-mail: ergolet@ergolet.dk Ergolet UK
The Courtyard
Wellington Road North
Stockport
Cheshire SK4 1HT
Tel: 0161 477 7900
e-mail: info@ergolet.co.uk

